



BASIC CLAMP:

The Basic (BAS.) repair clamp is a stripped down version of the Standard (STA) repair clamp. This means that only the necessary parts are on this clamp. All other parts and cost increasing actions are removed. There for this has a very competitive price level.

HEA. CLAMP:

If you come across a space problem while installing the clamp. the HEA. Clamp is the solution. Because of its removable closing mechanism you only need 10 mm of free space to install the clamp.

TC CLAMP:

This repair clamp is only partially covered with a NBR or EPDM gasket, suitable for repairing small holes in water pipelines. It is available in one section type and with a length of 100 or 150 mm.

SPECIFICATIONS:

- | | |
|---------------------|---|
| Bolts | - Stainless steel AISI 304 (A2); Dimensions depend on diameter. M12, M14 or M16 (metric thread according DIN267). |
| Lifterbar | - Stainless steel AISI 304 (A2). L shaped. Lips hold bolts in position while tightening. |
| Nuts | - Stainless steel AISI 304 (A2). Size M12, M14 or M16 according DIN934. Extra yellow passivated to optimize free running. |
| Body Shell | - Stainless steel AISI 304 (A2) |
| Armour plate | - Vulcanised into the gasket for all standard clamps Stainless steel AISI 304. not available on TC |
| Gasket | - NBR gasket, proper for both gas and water purposes. It has a waffle structure and tapered ends. EPDM gasket is optional. |
| Sidebar | - Stainless steel AISI 304 |
| Guide finger | - Stainless steel AISI 304, Guide fingers keep the bolts in position. |
| Additional | - Further to the above mentioned technical specifications; products are also available in AISI 316/316L quality. Not available on BASIC
- After welding all stainless steel parts are passivated to obtain a high corrosion resistance.
- Basis clamps are without labelling and not packed in a cardboard box. |

All mentioned working pressures on all our documents are only valid in optimum circumstances and based on document 2009.04.24.PRES-N002. please contact us for a copy of this document.

Tracon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tracon International BV takes no responsibility for printing errors.

Tacon International BV - Bossekamp 12 - 5301 LZ Zaltbommel - Tel: +31 418 84 00 03 - Fax: +31 418 84 00 04 - www.traconinternational.com