



SPECIFICATIONS:

This stainless steel restrain clamp is used for prevent a pipe connection to disconnect. Available in all different diameters upon request.

Thread protection Bolts

- Plastic caps to protect the thread.
- Stainless steel AISI 304 (A2); M16 (metric thread according DIN267). Thread is PTFE (Telfon™) coated to prevent galling.

Lifterbar Nuts

- Stainless steel AISI 304 (A2). L shaped. Lips hold bolts in position while tightening.
- Stainless steel AISI 304 (A2). Size M16 according DIN934. Extra yellow passivated to optimize free running.

Body Shell

- Stainless steel AISI 304 (A2).

Grip

- The inside of the Body shell is covered with a special heavy duty grip product.

Sidebar

- Stainless steel AISI 304.

Guide finger

- Stainless steel AISI 304, Guide fingers keep the bolts in position.

Additional

- After welding all stainless steel parts are passivated to obtain a high corrosion resistance.



An other solution in the same field is this custom made single part restrain clamp that is used for fixing all different brand of flange adaptors. All sizes are available upon request.



Tacon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tacon International BV takes no responsibility for printing errors.

Tacon International BV - Bossekamp 12 - 5301 LZ Zaltbommel - Tel: +31 418 84 00 03 - Fax: +31 418 84 00 04 - www.taconinternational.com