



DESCRIPTION:

This Easy to handle repair kit consists of 9 repair clamps. With this small box you can make repairs on any size of pipe varying between OD. 60 and OD. 170mm.

WORKING PRESSURE:

Pipe OD	working pressure (bar)	
	WATER	GAS
60 - 95	20	5
106 - 170	16	4

SPECIFICATIONS:

Bolts	- Stainless steel AISI 304 (A2); M14 (metric thread according DIN267). Thread is PTFE (Telfon™) coated to prevent galling.
Armour plate	- Stainless steel AISI 304, vulcanised into the gasket.
Gasket	- NBR gasket, proper for both gas and water purposes. It has a waffle structure and tapered ends.
Clamp width	- 200 mm.
Total weight box	- < 22 kg
Box dimensions	- 600 x 400 x 230 mm

Section	DN	Inch	Cast-Iron	Iron	Iron ISO-norm	PVC	Asbestos cement pipes, DIN 19800				
							PN 2,5	PN 6	PN 10	PN 12,5	PN 16
10	50	2	66	60,3	-	63	-	-	-	-	-
11	60	-	77	70	-	-	-	-	-	-	-
11	65	2 1/2	-	76,1	-	75	-	-	-	-	-
12	65	2 1/2	82	-	-	-	-	-	83	85	-
12	70	-	87	-	-	-	-	-	-	-	-
13	80	3	98	88,9	-	90	-	-	98	-	-
14	80	3	-	-	-	-	-	-	-	100	104
14	90	-	108	101,6	-	-	-	-	-	-	-
15	100	4	118	108	114,3	110	-	-	-	-	-
16	100	4	-	-	-	-	-	118	120	124	130
17	125	-	144	133	139,7	140	-	-	-	-	-
18	125	-	-	-	-	-	-	-	-	-	159
18	150	6	170	159	168,3	160	168	-	-	-	-

All mentioned working pressures on all our documents are only valid in optimum circumstances and based on document 2009.04.24.PRES-N002. please contact us for a copy of this document.

Tracon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tracon International BV takes no responsibility for printing errors.

Tacon International BV - Bossekamp 12 - 5301 LZ Zaltbommel - Tel: +31 418 84 00 03 - Fax: +31 418 84 00 04 - www.traconinternational.com