



These drilling Machines are designed for under pressure drilling with a maximum working pressure of 16 bar. Suitable for drilling ND 65 to ND 200. Available in 3 different sizes. DN65 - 100; DN 100 - 150; DN 150 - 200.

Drilling machines are suitable for Plastic, AC, Cast Iron and Ductile Iron.









Type: 106510

Nominal branch drill size - DN65 to DN100 incl. centre-bit **Power supply** 

TS 162 **Weight basic Machine** - 27,0 kg

- 1 phase current, 230 V/50 Hz, 1500 W

- 700 - 1400 rev/min.

1 unit base plate (aluminium).

2 units Part flanged DN 65 -100 and DN100-100 (aluminium).

- 2 units blind flanges DN 65 and DN 100 (aluminium).

- 2 pcs cutters for Plastic pipe Ø80 and Ø100

2 pcs cutters for cast iron pipe Ø80 and Ø100.



Type: 101015

Nominal branch drill size -**Power supply Weight basic Machine** 

Voltage Speed Including

Voltage

**Including** 

Speed

## DN100 to DN150 incl. centre-bit

- TS 252

- 33,0 kg

- 1 phase current, 230 V/50 Hz, 1900 W

- 450 - 900 rev/min.

- 1 unit base plate (aluminium).

- 2 units Part flanged DN 100 -150 and DN150-150 (aluminium).

- 2 units blind flanges DN 100 and DN 150

(aluminium).

2 pcs cutters for Plastic pipe Ø100 and Ø150

- 2 pcs cutters for cast iron pipe Ø100 and Ø150.

Tracon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tracon International BV takes no responsibility for printing errors.



Type: 101520

Nominal branch drill size -Power supply -

Weight basic Machine Voltage

Speed Including

Nominal branch drill size - DN150 to DN200 incl. centre-bit

TS 40245,0 kg

- 1 phase current, 230 V/50 Hz, 2800 W

- 300 - 700 rev/min.

- 1 unit base plate (aluminium).

- 2 units Part flanged DN 150-200 and DN200-200 (aluminium).

- 2 units blind flanges DN 150 and DN 200 (aluminium).

- 2 pcs cutters for Plastic pipe Ø150 and Ø200

- 2 pcs cutters for cast iron pipe Ø150 and Ø200.



Tracon International BV reserves the right to vary specifications or delete models from the range without prior notice. Tracon International BV takes no responsibility for printing errors.